

NEODECAPINT TOTAL

Multipurpose paint stripper for low/non-porous surfaces.



- ✓ **Low viscosity.**
- ✓ **Without chlorinated solvents.**
- ✓ **Fast and effective action.**
- ✓ **Multisurface.**
- ✓ **Quick drying.**

Description

Neodecapint Total is a low viscosity paint stripper free of chlorinated solvents designed for the removal of varnishes, glues, lacquers, paints and even asphalt remains on low or non-porous surfaces.

Neodecapint Total has a medium viscosity, giving it an optimal adhesion on the coating to be stripped, so it is suitable to be used on both vertical and horizontal surfaces. In addition, its special composition combines two different modes of action:

- On the one hand, this paint stripper effectively dissolves polymers from resins and paints in a few minutes, softening the coating and allowing it to be easily removable.
- On the other hand, Neodecapint Total passes through the coating and reaches the base of the same on the surface. At this point, it eliminates the adhesion of the coating, allowing it to peel off more easily.

This mode of action allows the process to be fully effective and fast without having to resort to highly toxic solvent-based products such as dichloromethane.

Neodecapint Total can be used on all types of surfaces, (except for plastics), since it does not chemically affect them. Therefore, it can be used on urban furniture of different materials, metals, wood, polished natural stone surfaces, etc.

Application Areas

Neodecapint Total is suitable for the removal of all types of coatings in: polished natural stone, porcelain materials, wood or metals varnished or lacquered, aluminium, etc.

NEODECAPINT TOTAL

Multipurpose paint stripper for low/non-porous surfaces.



Physical-Chemical Characteristics

APPEARANCE	DENSITY	COMPOSITION
Colourless clear liquid	1.03 ± 0.010 Kg/L	Non-halogenated solvents, alkalis, surfactants and thixotropic agents.

Mode of Application

Neodecapint Total is a ready to use product, therefore it does not require dilution before use.

- 1- Apply Neodecapint Total on the surface to be stripped, ensuring to spread a layer of 300-400 microns of the product.
- 2- Leave the product on for a few minutes. On non-porous surfaces it will be observed that the paint begins to deteriorate, losing gloss and wrinkles appear on the surface.
- 3- Then remove the stripped paint. Depending on the type of surface it can be performed with the aid of a spatula or scraper, or with a hydro-cleaner.
- 4- Finally, rinse the surface with a cloth dampened with water.

Format

Plastic container of 0.5L+Sprayer.
Industrial packaging: 5, 10 and 30 litres.



Recommendations

Keep away from any source of heat, ignition or sparks.
Keep out of reach of children.

Prior to using any stripper, it is recommended to perform a preliminary test to verify the full compatibility of the product with the surface.